

## 14. Hammasratasmootorid

### Hammasratasmootorid, rühm 2

Tüüp	Ringmahtuvus	Max töösurve	Täppissurve	Lited	Max. rpm
M 2 SMA 4	4,0 cm <sup>3</sup> /r	215 bar	250 bar	R 1/2"	4000
M 2 SMA 6	6,0 cm <sup>3</sup> /r	215 bar	250 bar	R 1/2"	4000
M 2 SMA 8	8,5 cm <sup>3</sup> /r	215 bar	250 bar	R 1/2"	3500
M 2 SMA 11	11,0 cm <sup>3</sup> /r	215 bar	250 bar	R 3/4"	3500
M 2 SMA 14	14,0 cm <sup>3</sup> /r	215 bar	250 bar	R 3/4"	3500
M 2 SMA 16	16,5 cm <sup>3</sup> /r	195 bar	210 bar	R 3/4"	3500
M 2 SMA 19	19,5 cm <sup>3</sup> /r	180 bar	195 bar	R 3/4"	3300
M 2 SMA 22	22,5 cm <sup>3</sup> /r	165 bar	180 bar	R 3/4"	2800
M 2 SMA 26	26,0 cm <sup>3</sup> /r	150 bar	165 bar	R 3/4"	2500

Lisateave: Kahele poolele pöörlevad mootorid (R), lekkeühendusega R 1/4

