

18. Hüdromootorid (planetaarreduktoriga)

Tüüp MMPM	cm ³ /r	Max vääne da Nm	Kasutussurve jätkuvs./hetks./täppiss.	Pöörded jätkuvs./hetks./täppiss.
MMPM 008NC16	8,2	1,1	140/175/225	1950/2440/50
MMPM 012NC16	12,9	1,6	140/175/225	1550/1940/40
MMPM 020NC16	20	2,5	140/175/225	1000/1250/30
MMPM 032NC16	31,8	4	140/175/225	630/790/30
MMPM 040NC16	40	4,1	140/175/225	500/625/25
MMPM 050NC16	50	4,5	140/175/225	400/500/20
Tüüp MMPP	cm ³ /r	Max vääne da Nm	Kasutussurve jätkuvs./hetks./täppiss.	Pöörded jätkuvs./hetks./täppiss.
MMPP 025NC25	25	3,3	175/200/225	1600/1800/20
MMPP 032NC25	32	4,3	175/200/225	1560/1720/15
MMPP 040NC25	40	6,2	175/200/225	1500/1700/10
MMPP 050NC25	49,5	7,9	175/200/225	1210/1515/10
MMPP 080NC25	79,2	13,2	175/200/225	755/945/10
MMPP 100NC25	99	16,4	175/200/225	605/755/10
MMPP 125NC25	123,8	20,5	175/200/225	486/605/10
MMPP 160NC25	158,4	26,4	175/200/225	378/472/10
MMPP 200NC25	198	26,5	175/200/225	303/378/10
MMPP 250NC25	247,5	27,6	175/200/225	242/303/10
MMPP 315NC25	316,8	29	175/200/225	190/236/10
MMPP 400NC25	396	28,5	175/200/225	150/189/10
MMPP 500NC25	495	32,5	140/175/225	120/150/10
MMPP 630NC25	623	36	140/175/225	95/120/10
Tüüp MMPR	cm ³ /r	Max vääne da Nm	Kasutussurve jätkuvs./hetks./täppiss.	Pöörded jätkuvs./hetks./täppiss.
MMPR 050NC25	51,5	10	175/200/225	775/970/20
MMPR 080NC25	80,3	16	175/200/225	750/940/10
MMPR 100NC25	99,8	20	175/200/225	600/750/10
MMPR 125NC25	125,7	25	175/200/225	475/600/10
MMPR 160NC25	159,6	28	175/200/225	375/470/10
MMPR 200NC25	199,8	29	175/200/225	300/375/10
MMPR 250NC25	250,1	30	175/200/225	240/300/10
MMPR 315NC25	315,7	30	175/200/225	190/240/10
MMPR 400NC25	397	30	175/200/225	150/190/10

Tihendiseeriad hüdmootoritele

Toode

Tihendiseeria

MEPMM

Tihendiseeria MEPM

Tihendiseeria

MEPRM

Tüüp	cm ³ /r	Max vääne da Nm	Kasutussurve jätkuvs./hetks./täppiss.	Pöörded jätkuvs./hetks./täppiss.
MMPS				
MMPS 080NC32	80,5	20	210/250/300	810/1000/10
MMPS 100NC32	100	25	210/250/300	750/900/10
MMPS 125NC32	125,7	32	210/250/300	600/720/10
MMPS 160NC32	159,7	34	210/250/300	470/560/10
MMPS 200NC32	200	40	210/250/300	375/450/10
MMPS 250NC32	250	45	210/250/300	300/360/10
MMPS 315NC32	314,9	54	210/250/300	240/285/10
MMPS 400NC32	397	58	210/250/300	185/225/10
MMPS 475NC32	474,6	58	210/250/300	160/190/10
MMPS 565NC32	564,9	58	210/250/300	130/160/10
Tüüp	cm³/r	Max vääne	Kasutussurve	Pöörded
MMPT		da Nm	jätkuvs./hetks./täppiss.	jätkuvs./hetks./täppiss.
MMPT 160NC40	116,1	47	210/250/300	625/780/10
MMPT 200NC40	201,4	59	210/250/300	625/750/9
MMPT 250NC40	251,8	73	210/250/300	500/600/8
MMPT 315NC40	326,3	95	210/250/300	380/460/7
MMPT 400NC40	410,9	108	210/250/300	305/365/6
MMPT 500NC40	523,6	122	210/250/300	240/285/5
MMPT 630NC40	612,3	123	210/250/300	206/247/5
MMPT 725NC40	725	125	210/250/300	172/205/5
Tüüp	cm³/r	Max vääne	Kasutussurve	Pöörded
MMPV		da Nm	jätkuvs./hetks./täppiss.	jätkuvs./hetks./täppiss.
MMPV 315C50	314,5	92	210/250/300	510/630/10
MMPV 400C50	400,9	118	210/250/300	500/600/9
MMPV 500C50	499,6	146	210/250/300	400/480/8
MMPV 630C50	629,1	166	210/250/300	315/380/6
MMPV 800C50	801,8	188	210/250/300	250/300/5

Roolijagajad

Tüüp	cm ³ /r	Max surge	Q
MHKUS 50/4	49,5	160 bar	5 l/min
MHKUS 63/4	65,6	160 bar	6 l/min
MHKUS 80/4	79,2	160 bar	9 l/min
MHKUS 100/4	99	160 bar	9 l/min
MHKUS 125/4	123,8	160 bar	12 l/min
MHKUS 160/4	158,4	160 bar	12 l/min
MHKUS 200/4	198	160 bar	17 l/min
MHKUS 250/4	247,5	160 bar	24 l/min
MHKUS 320/4	316,8	160 bar	30 l/min
MHKUS 400/4	396	160 bar	30 l/min

Juhthoob 75mm

150mm

Juhtrool

